

Vaso autoclave con membrana intercambiabile per circuiti di acqua sanitaria.  
 Pressure Tank with replaceable membrane for pressurized systems of sanitary water.  
 Réservoir sous pression à vessie remplaçable pour systèmes d'eau sanitaire.  
 Vaso agua fría con membrana recambiable para circuitos de agua sanitaria.

Marcati CE secondo la Direttiva **PED 2014/68/UE**  
 CE marked according to Directive  
 Avec le marque CE selon la Directive  
 Todos los vasos están marcados según la Directiva Europea

Colore della verniciatura esterna  
 External finish color  
 Couleur de la peinture externe  
 Pintura exterior

**RAL 5015**

Pressione di precarica standard  
 Standard pre-set pressure  
 Pression de precharge standard  
 Presión de precarga estándar

≤ 150

**1,5 bar**

> 150

**2 bar**

Pressione massima d'esercizio - Maximum working pressure  
 Pression maximale d'exercice - Presión máxima de trabajo


**10 bar**

Garanzia sul prodotto mesi: - Warranty months:  
 Garantie mois: - Garantía meses:

**24**



AO



AO

Modello Model Modèle Modelo	Codice Code Code Codigo	Altezza Height Hauteur Altura H (mm)	Diametro Diameter Diamètre Diámetro Ø (mm)	Lunghezza Lenght Longeur Longitud L (mm)	Membrana in gomma Rubber membrane Vessie en gomme Membrana en goma	Temperatura d'esercizio Working temperature Température d'exercice Temperatura de trabajo min MAX	Imballo Packing Emballage Embalaje P x L x H (mm)	Attacco Connection Raccordement Conexión (inch)
<b>A018</b>	IIGOE11B01CCO	305	280	430	EPDM	-10 °C +100 °C	(Pz 4) 520 x 580 x 610	1"
<b>A024</b>	IIIOE11B01ECO	305	280	485	EPDM	-10 °C +100 °C	(Pz 4) 520 x 580 x 610	1"
<b>A035</b>	IIJOE11B01EAO	376	365	440	EPDM	-10 °C +100 °C	(Pz 1) 380 x 400 x 460	1"
<b>A050</b>	IIKOE11B01EAO	380	365	585	EPDM	-10 °C +100 °C	(Pz 1) 380 x 400 x 575	1"
<b>A060</b>	IILOE11B01EAO	385	365	670	EPDM	-10 °C +100 °C	(Pz 1) 380 x 400 x 700	1"
<b>A080</b>	IIMOE11B01EAO	430	410	725	EPDM	-10 °C +100 °C	(Pz 1) 430 x 450 x 730	1"
<b>A0100</b>	IINOE11B11EAO	520	495	685	EPDM	-10 °C +100 °C	(Pz 1) 510 x 540 x 700	1"
<b>A0150</b>	IIPOE11B11EAO	585	550	820	EPDM	-10 °C +100 °C	(Pz 1) 570 x 610 x 850	1"
<b>A0200</b>	IIQOG21B11FA1	628	600	920	EPDM	-10 °C +100 °C	(Pz 1) 620 x 630 x 1030	1 ¼"
<b>A0300</b>	IISOG21B11FA1	680	650	1082	EPDM	-10 °C +100 °C	(Pz 1) 680 x 700 x 1290	1 ¼"

**Controflangia inox AISI 304 disponibile su richiesta.**  
**Stainless steel AISI 304 counter flange available on request.**  
**Contre bride inox AISI 304 disponible sur requête.**  
**Contra brida en acero inox AISI 304 bajo demanda.**