

Teava flexibila din inox ondulata paralel – tip THERMOINOX



- **Constructie: ondulata paralel**
- **Material: otel inox, 14404 (AISI316L)**
- **Domeniu de temperatura: -270...+600°C**
- **Presiune de operare la 110°C: 10...18 bar**



Sistem de conectare cu inel de siguranta si garnitura de klingerit

Permite racordarea simpla, rapida si eficienta a tevilor ondulate din inox folosite in montajul panourilor solare si sistemelor de incalzire: ventiloconvectoare, perdele de aer cald, aeroterme, boilere, CTA-uri



DN	DIAMETRU		RAZA DE INDOIRE		PRESIUNEA DE OPERARE LA 110°C (bar)	Masa /ml +/-10%(kg)	Echivalenta teava cupru
	d1 (mm) +/-0,4	d2/D (mm) +/-0,4	STATIC (mm)	DINAMIC (mm)			DN
12(1/2")	12,5	16,5	20	Nu si pentru sarcini dinamice si miscari frecvente corespunzatoare	18	0,09	15
16(3/4")	16,3	21,4	25		16	0,14	18
20(1")	20,4	26,7	30		16	0,19	22
25(1 1/4")	25,4	31,8	35		10	0,25	28

Importator si distribuitor autorizat: SC THERMOINOX SERVICE SRL 300639 Timisoara RO
thermoinox@thermoinox.ro +40(0) 721 788 816; +40(0) 721 640 340