

## Daikin Sensira FTXC-E cu adaptor WiFi integrat



### Specificatii tehnice

			20	25	35	50	60	71	
Model	Indoor Unit		FTXC20EV1B	FTXC25EV1B	FTXC35EV1B	FTXC50EV1B	FTXC60EV1B	FTXC71EV1B	
	Outdoor Unit		RXC20EV1B	RXC25EV1B	RXC35EV1B	RXC50EV1B	RXC60EV1B	RXC71EV1B	
Operating Limit	Cooling Heating	°C	10 ~ 46						
			15 ~ 18						
Cooling Capacity		kW	2,00	2,56	3,50	5,10	6,23	7,10	
Heating Capacity		kW	2,50	2,84	4,00	5,62	6,40	8,00	
EER (Cooling)		W/W	3,36	3,35	3,35	3,29	3,30	2,98	
COP (Heating)		W/W	3,73	3,79	3,74	3,71	3,81	3,25	
SEER (Cooling)		-	6,9 (A++)	6,8 (A++)	6,9 (A++)	6,5 (A++)	6,4 (A++)	5,3 (A)	
SCOP (Heating) Average Climate		-	4,4 (A+)	4,5 (A+)	4,3 (A+)	4,4 (A+)	4,2 (A+)	3,8 (A)	
SCOP (Heating) Warm Climate		-	5,8 (A+++)	5,8 (A+++)	5,7 (A+++)	5,3 (A+++)	5,4 (A+++)	4,6 (A++)	
Power Supply		V/Ph/Hz	220-240/1/50						
			Power from OUTDOOR						
Indoor Unit	Airflow (T/H/M/L/Q)	cfm	410/385/285/215/190	410/385/285/215/190	420/390/305/225/190	455/440/350/285/260	770/720/510/440/360	770/720/510/440/360	
	Sound Pressure Level (H/M/L/Q)	dB(A)	40/33/26/21	40/33/26/21	41/34/26/22	47/39/33/30	48/42/38/31	48/42/38/31	
	Unit Dimensions (HxWxD)	Unit	288 x 770 x 234						
		Packaging	314 x 830 x 357						
Machine Weight	Unit	kg	9	9	9,5	9,5	13	13	
Outdoor Unit	Sound Pressure Level	dB(A)	45	45	46	51	54	54	
Outdoor Unit	Dimensions (HxWxD)	Unit	550 x 658 x 273				615 x 845 x 300		695 x 930 x 350
		Packaging	610 x 781 x 363				679 x 992 x 414		760 x 1084 x 473
Piping Connections	Liquid Gas	mm	24	24	26	39	39	45	
		mm	6,4	6,4	6,4	6,4	6,4	6,4	
Maximum Piping Length		m	9,5	9,5	9,5	12,7	12,7	12,7	
Maximum Piping Elevation	Liquid Gas	m	20	20	20	30	30	30	
		m	15	15	15	20	20	20	